

Please read the enclosed Reno County Road Entrance and Culvert Policy carefully for understanding of the property owner's responsibility and the requirements to install a new entrance culvert onto a Reno County road.

In summation:

The enclosed application(s) must be completed and signed by the property owner. Please return the completed application(s) to our office located at 600 Scott Blvd., South Hutchinson, Kansas 67505. A \$50.00 application fee(s) will be due upon approval of application(s).

To assist the Engineering Techs in locating and confirming they are viewing and evaluating the correct site, please flag both ends of the proposed entrance.

Once the application has been reviewed, approved and payment of the application fee has been received, the original application will be returned to you with the required pipe size and length. **Before beginning construction, please adhere to the below notification requirements as set forth in the Policy.**

Notification requirements: Notify Reno County Public Works at 620-694-2976

- No less than 24 hours prior to beginning construction,
- No less than 24 hours prior to covering the culvert for inspection of proper grade of the culvert and end sections; and
- Upon completion of covering the culvert to inspect for proper coverage.

Construction for permanent entrances shall be completed AND approved by Reno County Public Works within 2 months of the permit issuance date. If construction is not completed within the 2-month deadline, an extension of time shall be requested by the property owner and may be approved at the Director's discretion before work resumes.

If you have any questions, please contact our office 620-694-2976.

Reno County Public Works

enclosures: County Road Entrance & Culvert Permit Application County Road Entrance & Culvert Policy

RENO COUNTY PUBLIC WORKS DEPARTMENT COUNTY ROAD ENTRANCE AND CULVERT PERMIT APPLICATION

Property Owner:			Contact I	Person:		
Mailing Address:				_ City:		Zip:
Telephone:		E	mail Address:			
Address or Location E	Description of P	roposed Entra	ance:			
Quarter: Section	on: Towr	nship:I	Range:			
	se side of this	permit for in	mportant detail	s. To m	nake a secure	rk each applicable box online credit/debit card
Note: Each entrance n considered as two ent						te fee. Circle drives are each.
	ANCE] TEMPORAF	RY ENTRANCE	E		MODIFICATION
Entrance Type: 🗌 F	Residential (18' – 22')		Business (30' – 40')] Other:	
Comments:						
Special Conditions: If	approved, entr	ances larger t	than 40' will red	quire a F	Poly Coated Co	rrugated Metal Pipe.
Is the proposed entran If yes, property owner floodplain regulations.	must contact t	he Reno Cour	nty Planning &	Zoning	Office to discus	s applicable zoning and
	d Entrance and	Culvert Polic	y and hold Ren	o Count		ns on attached standard any damage to applicant
Signature of Applicant **I understand by typ						e: his document.**
		OFF	ICE USE ONLY			
Permit No Inspection Fee: \$50.00 Permit Mailed Date:	Cash / Check N	No	er OR Credit /	Debit	Mile # Pymt Rcv'd By:	Twp
Initial Inspection:	(PW Ins	pector's initials)	Date Inspecti	on/Surve	y Completed:	
Pipe Size Required:		Pipe I	Length Required	:	with e	nd sections.
Comments:						
Application Approved By	/: Name		Title			Date
PM Director Approved:	Name		The			Date
PW Director Approved:	Name		Date)		
Final Inspection:		_	ufficient/Permit V		Entrance No	ot Installed/Permit Voided
Inspection By:			Date:			05 21 13 rev: 09 01 20: 04 01 21

RENO COUNTY PUBLIC WORKS DEPARTMENT COUNTY ROAD ENTRANCE AND CULVERT POLICY

POLICY:

This policy implements the provisions of KSA 68-543a. It is intended to provide requirements for the location and construction of private entrances onto county roads.

RESPONSIBILITY:

It shall be the responsibility of the Public Works Director to issue entrance permits for property owners to gain access onto county roads. No entrance from private property to a county road may be constructed or reconstructed without the Public Works Director's permission.

GENERAL:

New and reconstructed entrances require approval of location and size of structure required, if any, by the Public Works Director. If a structure is required, the minimum standard size will comply with Reno County's current standard, "Standards for Typical Resident, Commercial and Field Entrances" on file at the Public Works Department. Minimum standard size may be increased in size, depending on the amount of drainage, as determined by the Public Works Director. All permanent entrance installations require new corrugated metal pipe with end sections; therefore, no other types of pipe shall be allowed. Temporary culvert pipes are not required to be new and/or have end sections; however, size and type of pipe shall be approved by Reno County Public Works.

New shared entrances will not be allowed and no alterations of replacement or existing shared entrances to include change of type will be allowed.

A minimum space of 40 feet between property line and/or toe of the nearest entrance shall be required unless otherwise approved by the Public Works Director.

When the property owner is responsible for the costs of construction or reconstruction, the installation may be by either a local contractor or by the property owner.

If the property owner or contractor installs an entrance without a permit or the installation does not conform to county policy, then the entrance is subject to removal and replacement by the County at the property owner's expense.

If the County constructs or reconstructs a county roadway ditch and entrance improvements are required, the work will be done at the County's expense; EXCEPT, if the entrance had been constructed by the owner from after the effective date of this policy without a permit or contrary to the County's Entrance Culvert Policy, the property owner will pay for the cost of the entrance improvements.

A \$50.00 inspection fee will be required with all entrance permit applications.

PUBLIC SAFETY:

Due to intersection sight distances, entrances near the intersection of two public right-of-way lines will be allowed if outside of the sight triangle determined by the Public Works Director.

For safety and maintenance reasons, headwalls are not permitted.

During construction of an entrance, the property owner shall:

- 1. When working near or within the driving lane, construction work zone signs shall be required as per the current edition of the "Manual on Unified Traffic Control Devices" (MUTCD).
- 2. Store vehicles, construction equipment, materials, tools and debris off the right-of-way or a minimum of 30 feet from the edge of the roadway.
- 3. Maintain the roadway in good condition at all times. Repair any damage done to the roadway immediately. If dirt or mud is tracked onto the roadway, it shall be removed immediately to ensure the roadway is safe for the traveling public.
- 4. Patch damaged pavement as required by the Public Works Director. Saw cutting to provide a near patch may be required. Patch thickness shall match existing pavement thickness or a minimum 6" depth whichever is more. Patch material shall be BM-2 asphaltic concrete, properly compacted, or as otherwise directed by the Public Works Director.

UTILITIES:

Prior to commencing construction or reconstruction of an entrance and/or during the construction process, the property owner shall:

- 1. Notify Kansas One Call and obtain utility field locates (including those utilities that do not participate in Kansas One Call) in the anticipated work area before excavation.
- 2. Use work procedures that do not damage utilities or utility property within and adjacent to the work area.
- 3. Coordinate and perform work to avoid interrupting utility service.
- 4. Notify the utility owner of damage to or exposure of its utility property and not hinder the utility owner from restoring utility service.
- 5. Assume responsibility for damages to utilities arising from the installation of the entrance.

CONSTRUCTION REQUIREMENTS:

During the construction or reconstruction process, the property owner shall:

- 1. Comply with Reno County's current standard, "Standards for Typical Resident, Commercial and Field Entrances" on file at the Public Works Department.
- 2. Notify Reno County Public Works at 620-694-2976
 - No less than 24 hours prior to beginning construction,
 - No less than 24 hours prior to covering the culvert for inspection of proper grade of the culvert and end sections; and
 - Upon completion of covering the culvert to inspect for proper coverage.
- 3. Excavation. Beginning at the outlet end of the pipe and proceeding toward the upper end, excavate the bottom of the channel to the line, grade and elevation required. Construct the width of the trench sufficient to lay and backfill the pipe with a minimum width equal to the diameter of the pipe plus 6 inches on each side. Follow OSHA regulations for sloping the sides of the excavation.
- 4. Firm the foundation in the trench to prevent subsequent settlement by removing soft unstable materials and replacing with suitable materials.
- 5. If seeding is required by the Public Works Director, the following shall apply:
 - a. All disturbed areas shall be seeded, fertilized, and mulched in accordance with the following specifications.
 - b. Slopes and disturbed areas shall have a minimum 6" depth of soil suitable for supporting seed growth.
 - c. Before seeding, the entire area to be seeded shall be fertilized. The entire area shall then be raked to mix the fertilizer thoroughly into the upper 2" of soil.
 - d. Prairie hay mulch shall be uniformly spread over seeded areas to 1-1/2 inches loose depth.
- 6. Construction for permanent entrances shall be completed <u>and</u> approved by Reno County Public Works within 2 months of the permit issuance date. If construction is not completed within the 2-month deadline, an extension of time shall be requested by the property owner and may be approved at the Director's discretion before work resumes.

Construction <u>and</u> removal of temporary entrances shall be completed <u>and</u> approved by Reno County Public Works within 2 months of the permit issuance date. If construction and removal are not completed within the 2-month deadline, an extension of time shall be requested by the applicant and may be approved at the Director's discretion before work resumes. If an extension of time is approved, an additional \$50.00 inspection fee may be required for an extensive inspection to ensure proper drainage and entrance installation. After removal of the temporary entrance the applicant shall ensure that the ditch and Reno County road right-of-way be returned to original condition as before the temporary entrance was installed. If not returned to original condition, Reno County forces will complete this work and the applicant will be billed for all expenses incurred by Reno County. Temporary entrances without an extension and not removed within the 2-month deadline will be removed by Reno County forces and the applicant will be billed for all expenses incurred by Reno County.

EFFECTIVE DATE: This policy is adopted and shall be effective this 1^{st} day of <u>April</u>, 2021, and supersedes all previous policies.

Don Brittain Reno County Public Works Director


APPROVED:

Ron Hirst, Chairman Board of County Commissioners of Reno County, Kansas

ATTEST:

atton Anna

Reno County Clerk



To be determined by staff.

DETAILS

PIPE SLOPE: MATCH SLOPE OF DITCH OR AS SPECIFIED IN THE PERMIT.

3:1 SHOULDER SLOPE

ALL PIPES MUST BE NEW AT TIME OF PLACEMENT.

A space of 40' between property line or toe of nearest entrance is required.

CONSTRUCTION METHODS

BACKFILL WITH 6" COMPACTED LAYER, FILLING ON BOTH SIDES UNIFORMLY. PROVIDE MINIMUM 12" COMPACTED SOIL AND/OR ROCK/GRAVEL. ALL RCB'S SHALL REQUIRE WINGWALLS AND BE OF LIKE MATERIAL.

SPECIAL CONDITIONS

IF APPROVED, ENTRANCES LARGER THAN 40' WILL REQUIRE A POLY COATED CORRUGATED METAL PIPE.

Reno County Public Works

3 MIN

600 SCOTT BLVD SOUTH HUTCHINSON, KS 67505

STANDARDS FOR TYPICAL RESIDENT, COMMERCIAL, AND FIELD ENTRANCES

May 21, 2013